


Self-locking allen head pin D shackle - Dia 12 mm

Part #1306



Description

Self-locking shackle with allen head pin D forged in grade 316L stainless steel

The head of the pin does not stick out from the shackle body and thus eliminates any risk of snagging

No risks of loose due to vibrations

Outstanding working and breaking loads

WLL: only for industrial applications (lifting i.e...)

CE marking



Applications

Ideal to link chain and anchor

On the halyard, avoids to damage the sails

To be used when the clutter is reduced

Technical information

	Materials	316 stainless steel grade
	Working load (kg)	2080
	WLL (kg)	1200
	Breaking load (kg)	6000
	Weight (g)	187
	A (mm)	42
	B (mm)	27
	C (mm)	12
	D (mm)	24
	D diameter (mm)	12
	E (mm)	10
	F (mm)	73
	G (mm)	49

Caption



Working load (WL) : for nautical applications



Working Load Limit (WLL): for industrial applications only.
The safety factor is 5 times the breaking load.
 $WLL = \text{Breaking load} / 5$

Wichard strives to ensure, to the best of its ability, the accuracy and the update of the information disseminated on this document, and reserves the right to correct at any time and without notice the content, as well as to evolve its products.

In the case of an industrial application, please contact our sales and technical department to validate the use of these products. The request for certificates can be made directly with the sales department when ordering the products.

Non-contractual pictures.