

Safety data sheet  
according to UK REACH

Printing date 04.05.2026

Version number 18 (replaces version 17)

Revision: 04.05.2026

**SECTION 1: Identification of the substance/mixture and of the company/  
undertaking**

- 1.1 Product identifier
- Trade name: Epifanes Rapidcoat
- 1.2 Relevant identified uses of the substance or mixture and uses advised against
- Sector of Use
  - SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
  - SU21 Consumer uses: Private households / general public / consumers
- Environmental release category
  - ERC5 Use at industrial site leading to inclusion into/onto article
  - ERC8c Widespread use leading to inclusion into/onto article (indoor)
  - ERC8f Widespread use leading to inclusion into/onto article (outdoor)
- Application of the substance / the mixture
  - See our technical datasheet for application of this product.
  - See our technical datasheet for application of this product.
- Uses advised against
  - This product is not recommended for applications other than the uses identified above.
- 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:
  - W.Heeren & Zoon bv.
  - Oosteinderweg 32
  - 1432 AL Aalsmeer
  - Netherlands
  - tel.+31 297-360366
  - email: info@epifanes.nl
- Further information obtainable from: Research & Development.
- 1.4 Emergency telephone number: +61 7 5563 1222 (Monday-Friday 8:30am-5:00pm)

**SECTION 2: Hazards identification**

- 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 3                      H226 Flammable liquid and vapour.



GHS07

STOT SE 3                      H336 May cause drowsiness or dizziness.

Aquatic Chronic 3              H412 Harmful to aquatic life with long lasting effects.

- 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008
  - The product is classified and labelled according to the GB CLP regulation.

(Contd. on page 2)

Safety data sheet  
according to UK REACH

Printing date 04.05.2026

Version number 18 (replaces version 17)

Revision: 04.05.2026

Trade name: Epifanes Rapidcoat

(Contd. of page 1)

· Hazard pictograms



GHS02 GHS07

· Signal word Warning

· Hazard-determining components of labelling:

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, < 2% aromatics.

· Hazard statements

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· PBT:

The product does not meet the criteria for PBT in accordance with UK REACH Annex XIII.

Not applicable

· vPvB:

The product does not meet the criteria for vPvB in accordance with

UK REACH Annex XIII.

**SECTION 3: Composition/information on ingredients**

· 3.2 Mixtures

· Description:

Resin mixture

Solvent mixture with additives

(Contd. on page 3)

Safety data sheet  
according to UK REACH

Printing date 04.05.2026

Version number 18 (replaces version 17)

Revision: 04.05.2026

Trade name: Epifanes Rapidcoat

(Contd. of page 2)

· Dangerous components:

|                                                                                                    |                                                                                                                                                                                         |             |
|----------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------|
| CAS: 64742-48-9<br>EC number: 919-857-5<br>Index number: 649-327-00-6<br>Reg.nr.: 01-2119463258-33 | Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, < 2% aromatics.<br>Flam. Liq. 3, H226<br>Asp. Tox. 1, H304<br>STOT SE 3, H336<br>EUH066                                            | >40-<60%    |
| CAS: 68647-95-0<br>Reg.nr.: 01-2120099181-55                                                       | Fatty acids, C18-unsaturated, dimers, compounds, with coco alkylamines<br>STOT RE 2, H373<br>Aquatic Acute 1, H400; Aquatic Chronic 1, H410<br>Skin Irrit. 2, H315; Skin Sens. 1B, H317 | ≥0.25-≤0.5% |

· Additional information:

For the wording of the listed hazard phrases refer to section 16.

**SECTION 4: First aid measures**

- 4.1 Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Immediately rinse with water.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: Seek medical treatment.
- 4.2 Most important symptoms and effects, both acute and delayed  
No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed  
No further relevant information available.

**SECTION 5: Firefighting measures**

- 5.1 Extinguishing media
- Suitable extinguishing agents:  
CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water
- 5.2 Special hazards arising from the substance or mixture  
During heating or in case of fire poisonous gases are produced.  
No further relevant information available.
- 5.3 Advice for firefighters
- Protective equipment: Mouth respiratory protective device.

GB

(Contd. on page 4)

Safety data sheet  
according to UK REACH

Printing date 04.05.2026

Version number 18 (replaces version 17)

Revision: 04.05.2026

Trade name: Epifanes Rapidcoat

(Contd. of page 3)

**SECTION 6: Accidental release measures**

- 6.1 Personal precautions, protective equipment and emergency procedures  
Ensure adequate ventilation  
Mount respiratory protective device.  
Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions:  
Prevent seepage into sewage system, workpits and cellars.  
Inform respective authorities in case of seepage into water course or sewage system.  
Dilute with plenty of water.  
Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to section 13.  
Ensure adequate ventilation.
- 6.4 Reference to other sections  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

**SECTION 7: Handling and storage**

- 7.1 Precautions for safe handling  
Work only in fume cupboard.  
Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.
- Information about fire - and explosion protection:  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.  
Keep respiratory protective device available.
- 7.2 Conditions for safe storage, including any incompatibilities
- Storage:  
Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required
- Further information about storage conditions: Keep container tightly sealed.
- 7.3 Specific end use(s) No further relevant information available.

**SECTION 8: Exposure controls/personal protection**

- 8.1 Control parameters
- Ingredients with limit values that require monitoring at the workplace:  
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

(Contd. on page 5)

**Safety data sheet  
according to UK REACH**

Printing date 04.05.2026

Version number 18 (replaces version 17)

Revision: 04.05.2026

Trade name: Epifanes Rapidcoat

(Contd. of page 4)

· DNEL (Derived No Effect Level) voor professionals

64742-48-9 Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, &lt; 2% aromatics.

|            |                               |                                  |
|------------|-------------------------------|----------------------------------|
| Oral       | Long-term - systemic effects. | 125 mg/kg bw/dag (consumer)      |
| Dermal     | Long-term - systemic effects. | 125 mg/kg bw/dag (consumer)      |
| Inhalative | Long-term - systemic effects. | 185 mg/m <sup>3</sup> (consumer) |

68647-95-0 Fatty acids, C18-unsaturated, dimers, compounds, with coco alkylamines

|            |                               |                                    |
|------------|-------------------------------|------------------------------------|
| Oral       | Long-term - systemic effects. | 0.13 mg/kg bw/dag (consumer)       |
| Dermal     | Long-term - systemic effects. | 0.25 mg/kg bw/dag (consumer)       |
|            | Long-term - local effects.    | 86.5 µg/cm <sup>2</sup> (consumer) |
| Inhalative | Long-term - systemic effects. | 0.45 mg/m <sup>3</sup> (consumer)  |

· DNEL (Derived No Effect Level) for general audience

64742-48-9 Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, &lt; 2% aromatics.

|            |                                     |                                   |
|------------|-------------------------------------|-----------------------------------|
| Dermal     | Long-term - systemic effects.       | 208 mg/kg/dag (Employees)         |
| Inhalative | Lange termijn systemische effecten. | 871 mg/m <sup>3</sup> (Employees) |

68647-95-0 Fatty acids, C18-unsaturated, dimers, compounds, with coco alkylamines

|            |                                     |                                    |
|------------|-------------------------------------|------------------------------------|
| Dermal     | Long-term - systemic effects.       | 0.51 mg/kg/dag (Employees)         |
| Inhalative | Lange termijn systemische effecten. | 0.91 mg/m <sup>3</sup> (Employees) |

· PNECs

68647-95-0 Fatty acids, C18-unsaturated, dimers, compounds, with coco alkylamines

|                         |                                                    |
|-------------------------|----------------------------------------------------|
| Freshwater              | 0 mg/l (Freshwater)                                |
| Marine water            | 0 mg/l (Marine water)                              |
| Sediment (freshwater)   | 0.04 mg/kg sed dw (Freshwater)                     |
| Sediment (marine water) | 0.004 mg/kg sed dw (Freshwater)                    |
| STP                     | 180 mg/l (Segmentation, Targeting and Positioning) |
| Soil                    | 2 mg/kg (soil)                                     |

· Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

- Appropriate engineering controls No further data; see section 7.
- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:  
Do not eat, drink, smoke or sniff while working.  
Immediately remove all soiled and contaminated clothing  
Wash hands before breaks and at the end of work.

· Respiratory protection:

Filter AX

In case of short or low load, breathing filter device; in the case of intensive or prolonged exposure, use a breathing apparatus independent of the surrounding air. A half-face mask for organic vapours and solvents according to EN140 type

(Contd. on page 6)

Safety data sheet  
according to UK REACH

Printing date 04.05.2026

Version number 18 (replaces version 17)

Revision: 04.05.2026

Trade name: Epifanes Rapidcoat

(Contd. of page 5)

A1 or A2 is recommended.

· Hand protection

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· For the permanent contact gloves made of the following materials are suitable: nitrile rubber;

recommended glove thickness > 0.45mm. permeability / permeation time: > 480 min. according to EN 374.

· As protection from splashes gloves made of the following materials are suitable:

Cloropene; handglove thickness > 0.7mm, penetration time > 60min. according EN374.

Nitrilrubber; handglove thickness > 0.3mm, penetration time > 60min. according EN374.

· Eye/face protection



Tightly sealed goggles

· Body protection: Use protective suit.

· Environmental exposure controls

Keep container tightly closed when not in use regarding restrictions on emissions to air, water and soil.

**SECTION 9: Physical and chemical properties**

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state

Liquid

· Colour:

Character

· Odour:

Characteristic

(Contd. on page 7)

Safety data sheet  
according to UK REACH

Printing date 04.05.2026

Version number 18 (replaces version 17)

Revision: 04.05.2026

Trade name: Epifanes Rapidcoat

(Contd. of page 6)

|                                                            |                                                                                     |
|------------------------------------------------------------|-------------------------------------------------------------------------------------|
| · Odour threshold:                                         | Not determined                                                                      |
| · Melting point/freezing point:                            | Undetermined                                                                        |
| · Boiling point or initial boiling point and boiling range | 154 °C (Koolwaterstoffen, C9-C11, n-alkanen, isoalkanen, cyclische, < 2% aromaten.) |
| · Flammability                                             | Flammable.                                                                          |
| · Lower and upper explosion limit                          |                                                                                     |
| · Lower:                                                   | 0.6 Vol %                                                                           |
| · Upper:                                                   | 7 Vol %                                                                             |
| · Flash point:                                             | 36 °C                                                                               |
| · Auto-ignition temperature:                               | 240 °C                                                                              |
| · Decomposition temperature:                               | Not determined                                                                      |
| · pH                                                       | Mixture is non-soluble (in water).                                                  |
| · Viscosity:                                               |                                                                                     |
| · Kinematic viscosity at 20 °C                             | 25 s (DIN 53211/4)                                                                  |
| · Dynamic:                                                 | Not determined                                                                      |
| · Solubility                                               |                                                                                     |
| · water:                                                   | Fully miscible.                                                                     |
| · Partition coefficient n-octanol/water (log value)        | Not determined                                                                      |
| · Vapour pressure:                                         | Not determined                                                                      |
| · Density and/or relative density                          |                                                                                     |
| · Density at 20 °C:                                        | 0.894 g/cm <sup>3</sup> (ISO 2811)                                                  |
| · Relative density                                         | Not determined                                                                      |
| · Vapour density                                           | Not determined                                                                      |

|                                                                                 |                                                                                             |
|---------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------|
| · 9.2 Other information                                                         |                                                                                             |
| · Appearance:                                                                   |                                                                                             |
| · Form:                                                                         | Fluid                                                                                       |
| · Important information on protection of health and environment, and on safety. |                                                                                             |
| · Ignition temperature:                                                         | Product is not selfigniting.                                                                |
| · Explosive properties:                                                         | Product is not explosive. However, formation of explosive air/vapour mixtures are possible. |
| · Solvent content:                                                              |                                                                                             |
| · Organic solvents:                                                             | 55.8 %                                                                                      |
| · VOC content:                                                                  | 55.85 %                                                                                     |
|                                                                                 | VOC content:                                                                                |
|                                                                                 | 499.3 g/l / 4.17 lb/gal                                                                     |
| · Solids content:                                                               | 41.6 % (VB% 1h 150C)                                                                        |
| · Change in condition                                                           |                                                                                             |
| · Evaporation rate                                                              | Not determined                                                                              |

|                                                      |      |
|------------------------------------------------------|------|
| · Information with regard to physical hazard classes |      |
| · Explosives                                         | Void |
| · Flammable gases                                    | Void |

(Contd. on page 8)

Safety data sheet  
according to UK REACH

Printing date 04.05.2026

Version number 18 (replaces version 17)

Revision: 04.05.2026

Trade name: Epifanes Rapidcoat

(Contd. of page 7)

|                                                                             |                              |
|-----------------------------------------------------------------------------|------------------------------|
| · Aerosols                                                                  | Void                         |
| · Oxidising gases                                                           | Void                         |
| · Gases under pressure                                                      | Void                         |
| · Flammable liquids                                                         | Flammable liquid and vapour. |
| · Flammable solids                                                          | Void                         |
| · Self-reactive substances and mixtures                                     | Void                         |
| · Pyrophoric liquids                                                        | Void                         |
| · Pyrophoric solids                                                         | Void                         |
| · Self-heating substances and mixtures                                      | Void                         |
| · Substances and mixtures, which emit flammable gases in contact with water | Void                         |
| · Oxidising liquids                                                         | Void                         |
| · Oxidising solids                                                          | Void                         |
| · Organic peroxides                                                         | Void                         |
| · Corrosive to metals                                                       | Void                         |
| · Desensitised explosives                                                   | Void                         |

**SECTION 10: Stability and reactivity**

- 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:  
No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid  
Avoid heat, flames and other sources of ignition. Static electricity and spark formation should be avoided. Do not pressurise, cut, weld, drill, abrade or otherwise expose to heat or sources of ignition.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products:  
No dangerous decomposition products known.

**SECTION 11: Toxicological information**

- 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- Acute toxicity Void

- LD/LC50 values relevant for classification:

64742-48-9 Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, < 2% aromatics.

|            |              |                                          |
|------------|--------------|------------------------------------------|
| Oral       | LD50         | >5,000 mg/kg (rat) (OESO 401)            |
| Dermal     | LD50         | >5,000 mg/kg (rabbit) (OESO 402)         |
| Inhalative | LC50 4 hours | 4,951 mg/m <sup>3</sup> (rat) (OESO 403) |

- Primary irritant effect:
- Skin corrosion/irritation Void

(Contd. on page 9)

Safety data sheet  
according to UK REACH

Printing date 04.05.2026

Version number 18 (replaces version 17)

Revision: 04.05.2026

Trade name: Epifanes Rapidcoat

(Contd. of page 8)

- Serious eye damage/irritation Void
- Respiratory or skin sensitisation  
Based on available data, the classification criteria are not met.
- Germ cell mutagenicity Void
- Carcinogenicity  
Based on available data, the classification criteria are not met.
- Reproductive toxicity  
Based on available data, the classification criteria are not met.
- STOT-single exposure May cause drowsiness or dizziness.
- STOT-repeated exposure  
Based on available data, the classification criteria are not met.
- 11.2 Information on other hazards

· Endocrine disrupting properties

None of the ingredients is listed.

**SECTION 12: Ecological information**

· 12.1 Toxicity

· Aquatic toxicity:

64742-48-9 Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, < 2% aromatics.

|               |                               |
|---------------|-------------------------------|
| LC50 48 hours | 1,000 mg/l (Water fleas)      |
| LL50 96 hours | >1,000 mg/l ((Rainbow trout)) |
| NOELR 72 uur  | 100 mg/l (Microalgae)         |
| EL50 72 hours | 1,000 mg/l (Microalgae)       |

- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- PBT:  
This substance is not classified as PBT or vPvB according to current EU criteria.
- vPvB:  
This substance is not classified as vPvB according to current EU criteria.
- 12.6 Endocrine disrupting properties  
The product does not contain substances with endocrine disrupting properties.
- 12.7 Other adverse effects
- Remark: Harmful to fish
- Additional ecological information:
- General notes:  
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water  
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

(Contd. on page 10)

Safety data sheet  
according to UK REACH

Printing date 04.05.2026

Version number 18 (replaces version 17)

Revision: 04.05.2026

Trade name: Epifanes Rapidcoat

Harmful to aquatic organisms

(Contd. of page 9)

**SECTION 13: Disposal considerations**

- 13.1 Waste treatment methods
- Recommendation  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.
- Recommended cleansing agents:  
Water, if necessary together with cleansing agents.

**SECTION 14: Transport information**

- |                                                                                     |                             |
|-------------------------------------------------------------------------------------|-----------------------------|
| • 14.1 UN number or ID number                                                       |                             |
| • ADR, IMDG, IATA                                                                   | UN1263                      |
| • 14.2 UN proper shipping name                                                      |                             |
| • ADR                                                                               | 1263 PAINT                  |
| • IMDG, IATA                                                                        | PAINT                       |
| • 14.3 Transport hazard class(es)                                                   |                             |
| • ADR                                                                               |                             |
|  |                             |
| • Class                                                                             | 3 (F1) Flammable liquids.   |
| • Label                                                                             | 3                           |
| • IMDG, IATA                                                                        |                             |
|  |                             |
| • Class                                                                             | 3 Flammable liquids.        |
| • Label                                                                             | 3                           |
| • 14.4 Packing group                                                                |                             |
| • ADR, IMDG, IATA                                                                   | III                         |
| • 14.5 Environmental hazards:                                                       |                             |
| • Marine pollutant:                                                                 | No                          |
| • 14.6 Special precautions for user                                                 | Warning: Flammable liquids. |

(Contd. on page 11)

Safety data sheet  
according to UK REACH

Printing date 04.05.2026

Version number 18 (replaces version 17)

Revision: 04.05.2026

Trade name: Epifanes Rapidcoat

(Contd. of page 10)

|                                                                |                                                                                                                        |
|----------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------|
| · Hazard identification number (Kemler code):                  | 30                                                                                                                     |
| · EMS Number:                                                  | F-E, S-E                                                                                                               |
| · Stowage Category                                             | A                                                                                                                      |
| · 14.7 Maritime transport in bulk according to IMO instruments | Not applicable                                                                                                         |
| · Transport/Additional information:                            |                                                                                                                        |
| · ADR                                                          |                                                                                                                        |
| · Limited quantities (LQ)                                      | 5L                                                                                                                     |
| · Excepted quantities (EQ)                                     | Code: E1<br>Maximum net quantity per inner packaging:<br>30 ml<br>Maximum net quantity per outer packaging:<br>1000 ml |
| · Transport category                                           | 3                                                                                                                      |
| · Tunnel restriction code                                      | D/E                                                                                                                    |
| · IMDG                                                         |                                                                                                                        |
| · Limited quantities (LQ)                                      | 5L                                                                                                                     |
| · Excepted quantities (EQ)                                     | Code: E1<br>Maximum net quantity per inner packaging:<br>30 ml<br>Maximum net quantity per outer packaging:<br>1000 ml |
| · UN "Model Regulation":                                       | UN 1263 PAINT, 3, III                                                                                                  |

**SECTION 15: Regulatory information**

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Poisons Act

- Regulated explosives precursors

None of the ingredients is listed.

- Regulated poisons

None of the ingredients is listed.

- Reportable explosives precursors

None of the ingredients is listed.

- Reportable poisons

None of the ingredients is listed.

- Directive 2012/18/EU
- Named dangerous substances - ANNEX I None of the ingredients is listed.
- Seveso category P5c FLAMMABLE LIQUIDS

(Contd. on page 12)

GB

Safety data sheet  
according to UK REACH

Printing date 04.05.2026

Version number 18 (replaces version 17)

Revision: 04.05.2026

Trade name: Epifanes Rapidcoat

(Contd. of page 11)

- Qualifying quantity (tonnes) for the application of lower-tier requirements  
5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements  
50,000 t
- National regulations:
- Technical instructions (air):

| Class | Share in % |
|-------|------------|
| NK    | 50-100     |

- 15.2 Chemical safety assessment:  
A Chemical Safety Assessment has not been carried out.

**SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Relevant phrases
  - H226 Flammable liquid and vapour.
  - H304 May be fatal if swallowed and enters airways.
  - H315 Causes skin irritation.
  - H317 May cause an allergic skin reaction.
  - H336 May cause drowsiness or dizziness.
  - H373 May cause damage to organs through prolonged or repeated exposure.
  - H400 Very toxic to aquatic life.
  - H410 Very toxic to aquatic life with long lasting effects.
  - EUH066 Repeated exposure may cause skin dryness or cracking.
- Classification according to Regulation (EC) No 1272/2008  
The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.
- Department issuing SDS: Research & Development.
- Contact: J.J. van Dijk, tel: +31 297 360678, email: rend@epifanes.nl
- Abbreviations and acronyms:
  - RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
  - ICAO: International Civil Aviation Organisation
  - ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
  - IMDG: International Maritime Code for Dangerous Goods
  - IATA: International Air Transport Association
  - GHS: Globally Harmonised System of Classification and Labelling of Chemicals
  - EINECS: European Inventory of Existing Commercial Chemical Substances
  - ELINCS: European List of Notified Chemical Substances
  - CAS: Chemical Abstracts Service (division of the American Chemical Society)
  - VOC: Volatile Organic Compounds (USA, EU)
  - DNEL: Derived No-Effect Level (UK REACH)
  - PNEC: Predicted No-Effect Concentration (UK REACH)
  - LC50: Lethal concentration, 50 percent
  - LD50: Lethal dose, 50 percent
  - PBT: Persistent, Bioaccumulative and Toxic

(Contd. on page 13)

**Safety data sheet  
according to UK REACH**

Printing date 04.05.2026

Version number 18 (replaces version 17)

Revision: 04.05.2026

**Trade name: Epifanes Rapidcoat**

(Contd. of page 12)

vPvB: very Persistent and very Bioaccumulative

ATE: Acute toxicity estimate values

Flam. Liq. 3: Flammable liquids - Category 3

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Skin Sens. 1B: Skin sensitisation - Category 1B

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

· **Sources**

ECHA European Chemical Agency - <http://echa.europa.eu/information-on-chemicals>  
SDS of raw materials provided by producer/supplier.

DNEL/PNEC/Aquatic toxicity provided according to safety data sheet producer/  
supplier.

- \* Data compared to the previous version altered.