

Non-Slip Additive

Special Products

Slip Resistant Additive



PRODUCT DESCRIPTION

A synthetic granular material that can be added to topside finishes prior to application or sprinkled onto wet paint as an aid to providing a more slip-resistant finish.

- * Provides a slip resistant finish when added to or sprinkled onto paint
- * Does not affect finish drying times
- * Allows finish to still be applied as standard

PRODUCT INFORMATION

Colour	YMA905
Specific Gravity	0.9
Volume Solids	100%
VOC (As Supplied)	0 g/lit
Unit Size	23 g sachet (x 12)

DRYING/OVERCOATING INFORMATION

Drying

Note: Touch Dry is the same as for the Finish.

Overcoating Substrate Temperature

Overcoated By	5°C (41°F)		10°C (50°F)		23°C (73°F)		35°C (95°F)	
	Min	Max	Min	Max	Min	Max	Min	Max

Note: Overcoating Times are the same as for the Finish.

APPLICATION AND USE

Preparation	All substrates must be clean, dry and free from contaminants. GENERAL APPLICATION: Mix-in method - Add to topcoat and stir. Apply by brush, roller or spray. To apply to wet paint - Apply one coat of topcoat. Apply Non-Slip Additive with a suitable dispenser or other dispersion method until desired grit onto surface has been achieved. Allow to fully cure and remove excess grit.
Hints	Mixing The amount to mix is dependent on the non-skid texture desired. Stir Non-Slip Additive into topcoat thoroughly. Thinner Same as for finish. Cleaner Same as for finish. Ventilation and Humidity Control Ensure adequate ventilation during use.
Compatibility/Substrates	Compatible with International Topcoats.
Coverage	(Theoretical) - 10 m ² /L per coat 8-12m ² /lit when spread manually
Application Methods	Brush, Conventional Spray, Roller or apply directly onto wet paint.

TRANSPORTATION, STORAGE AND SAFETY INFORMATION

Storage	TRANSPORTATION: Non-Slip Additive should be kept in securely closed containers during transport and storage. STORAGE: Exposure to air and extremes of temperature should be avoided. For the full shelf life of this product to be realised ensure that between use the container is firmly closed and the temperature is between 5°C/41°F and 35°C/95°F. Keep out of direct sunlight.
Safety	DISPOSAL: Do not discard tins or pour paint into water courses, use the facilities provided. It is best to allow paints to harden before disposal. GENERAL: Read the label safety section for Health and Safety Information, also available from our Technical Help Line. Always use gloves and goggles and keep skin protected with overalls. Users should ensure they have a copy of the Material Safety Datasheet for this product and that they are familiar with all the safety directions before use.
IMPORTANT NOTES	<i>The technical information and suggestions for use and application presented herein are not intended to be exhaustive.</i>

Please refer to your local representative or visit www.yachtpaint.com for further information.

All trademarks mentioned in this publication are owned by, or licensed to, the AkzoNobel group of companies. © AkzoNobel 2018.

Non-Slip Additive
Special Products
Slip Resistant Additive



but they represent the best information available to use and are believed to be reliable. They should not, however, be construed as controlling suggestions and there is no warranty of performance of our materials either expressed or implied. We urge that users of our materials conduct confirmatory tests to determine final suitability for their specific end uses. Because this datasheet is subject to changes from time to time, it is the user's responsibility to check that this sheet is current prior to using the product.

Please refer to your local representative or visit www.yachtpaint.com for further information.

All trademarks mentioned in this publication are owned by, or licensed to, the AkzoNobel group of companies. © AkzoNobel 2018.