

34060-0010 'LITTLE PAL'

JABSCO hand pumps pump more liquid with less effort! They never need coaxing or priming and give full suction on the first stroke. Pumps can be used in any position.

Uses include bilge pumping, oil draining, diesel fuel transfer, and many other liquid transfer applications. NOTE: Oil temperature should not exceed 60° C.

Long life brass cylinders, high quality oil resistant plungers, intake and discharge caps are used. Hoses included with all models.

SPECIFIC	CATIONS	
		-

Model	Output	Strokes Per litre	Cylinder Dia	Stroke Length	Overall Length	Hose Connections	Hose Supplied	Weight
33799- 0000 HANDY BOY	Up to 7 litres/min (1½ gall/min)	6	30mm dia	190mm	305mm	Outlet 13mm (1/2" bore hose) plus inlet adaptor of same size	0.9m of 13mm 1m of 6mm 1m of 8mm	900g
34060- 0010 LITTLE PAL	Up to 5 litres/min (1 gall/min)	9	30mm dia	117mm	260mm	13mm (1/2" bore hose)	0.6m of 13mm 1m of 6mm	500g

PUMPS USED IN DIESEL FUEL APPLICATIONS MUST BE FLUSHED CLEAN AFTER USE TO PREVENT NEOPRENE PART DISTORTION.



Explosive hazard. Do not pump gasoline, solvents, thinners or other flammable liquids. To do so can cause an explosion resulting in injury or death



Xylem Water Solutions UK Ltd Bingley Road • Hoddesdon • Hertfordshire • EN11 0BU • UK Telephone: +44 (0)1462 480380 Fax: +44 (0)1462 482422 mail@cleghorn.co.uk www.jabscoshop.com

DOC561/11