

Marlow ^{DATASHEET}®

CHAFE COVER



CONSTRUCTION

MATERIAL: Dyneema SK75 (high modulus polyethylene)
CONSTRUCTION: Hollow braided rope
COATING: 'Armourcoat' PU impregnation available

PROPERTIES

LIGHT WEIGHT: Easily handled
LOW FRICTION:
CUT RESISTANT FIBRE: Very good abrasion resistance
ARMOURCOATED: Improves abrasion resistance and feel
GOOD UV RESISTANCE: Durable and suitable for outdoor use
EXCELLENT CHEMICAL RESISTANCE: Resistant to most common chemicals

PERFORMANCE

DIAMETER		MASS		PLAITS	MIN DIAMETER		MAX DIAMETER	
mm	Inch	g/m	lb/100 ft		mm	Inch	mm	Inch
8	5/16	15	1.01	32	4	5/32	10	13/16
10	13/16	22	1.48	32	5	3/16	14	9/16
10	13/16	20	1.34	48	6	7/32	16	5/8
12	15/32	32	2.15	48	7	1/4	18	3/4
14	9/16	42	2.82	48	9	3/8	20	13/16
16	5/8	52	3.49	48	11	7/16	24	15/16
20	13/16	72	4.83	48	14	9/16	28	1 1/8

Marlow Ropes Ltd
Ropemaker Park
Hailsham
East Sussex, BN27 3GU
England

Marlow Ropes, Inc.
Cordage Business Park
Plymouth
MA 02360
USA

www.marlowropes.com
UK: +44 (0) 1323 444 444
sales@marlowropes.com
US: +1 508 830 444
salesusa@marlowropes.com

Disclaimer

Marlow Ropes Ltd endeavours to ensure that all products are manufactured to the highest standard, these guidelines are not intended and do not create any warranties, express or implied.
Marlow Ropes Ltd expressly disclaims warranties or representations of any kind, express or implied, including the implied warranties of merchantability and fitness for a particular purpose.
Marlow Ropes Ltd shall not be liable for any consequential, incidental or contingent damages whatsoever stemming from the use of these guidelines.
Marlow Ropes Ltd has a policy of continual improvement which may result in specification and colour changes without prior notice.

