SAFETY DATA SHEET



1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: STAR BRITE FOGGING OIL #084812

NAME AND ADDRESS OF RESPONSIBLE PARTY:

Star brite Inc. 4041 SW 47th Avenue Fort Lauderdale, FL 33314 (954)587-6280 www.starbrite.com

EMERGENCY PHONE : US: (800) 424-9300; International: (703) 527-3887 (CHEMTREC)

INFORMATION PHONE: (954)587-6280
Product Use: Engine storage lubricant

2. HAZARDS IDENTIFICATION

CLASSIFICATION

Flammable aerosol

Gas under pressure Liquefied gas

Skin Corrosion/Irritation







SIGNAL WORD:

Danger

Hazard Statements

Extremely flammable aerosol

Contains gas under pressure; may explode if heated

Causes mild skin irritation

Precautionary Statements

Keep away from heat/sparks/open flames/hot surfaces - No smoking

Do not spray on an open flame or other igntion source

Pressurized container – Do not pierce or burn, even after use

If skin irritation occurs: Get medical advice/attention Protect from sunlight. Store in a well ventilated place

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No.	Percent
PETROLEUM OIL	64742-52-5	62.70
BUTANE	106-97-8	23.10
PROPANE	74-98-6	11.90
PETROLUEM OIL	64742-53-6	1.50

4. FIRST AID MEASURES

INHALATION: Remove to fresh air. Administer oxygen if needed. Apply artificial respiration if breating has stopped. Get medical attention.

EYE CONTACT: Wash immediately with large volumes of fresh water for at least 15 minutes. Get medical attention.

SKIN CONTACT: Wipe off with a towel. Wash with soap and water. Get medical attention if irritation persists.

INGESTION: Not a likely route of exposure.

Most important symptoms/effects, acute and delayed: Repeated exposure may cause skin dryness or cracking. May cause drowsiness or dizziness.

Indication of immediate medical attention and special treatment needed: None known.

5. FIRE FIGHTING MEASURES

Suitable and unsuitable extinguising media: Foam, Alcohol foam, CO2, Dry chemical, Water fog. Water spray may be ineffective.

Specific hazards arising from the chemical: Closed containers may explode from internal pressure build-up when exposed to extreme heat and discharge contents. Liquid content of container will support combustion. Overexposure to decomposition products may cause a health hazard. Symptoms may not be readily apparent. Obtain medical attention. Hazardous decomposition products include carbon dioxide, carbon monoxide, and other toxic fumes.

Special equipment and precautions for fire-fighters: Water may be used to cool containers to prevent pressure build-up and explosion when exposed to extreme heat. Wear goggles and use self-contained breathing apparatus. If water is used, fog nozzles are preferred.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment, and emergency procedures: Avoid breathing vapors. Ventilate area. Remove all sources of ignition.

Methods and materials for containment and cleaning up: Clean up with absorbent material and place in closed containers for disposal.

7. HANDLING AND STORAGE

Precautions for safe handling: Do not puncture or incinerate (burn) cans. Do not stick pins, nails, or any other sharp objects into opening on top of can. Do not spray in eyes. Do not take internally. See product label for additional information.

Conditions for safe storage, including any incompatibilities: Store and use in cool, dry, well-ventilated areas. Do not store above 120 F.

8. EXPOSURE CONTROL/PERSONAL PROTECTION

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
PETROLEUM OIL	PEL: Mist 5 mg/m3, 8 hrs	TLV: Mist 5 mg/m3, 8 hrs	
64742-52-5			
BUTANE	Not established	TWA: 1000 ppm	
106-97-8			
PROPANE	Not established	TWA: 1000 ppm	
74-98-6			

AIMITET-CC Page 2 of 4

PETROLUEM OIL		
64742-53-6		

Appropriate engineering controls: Ventilation should be sufficient to prevent inhalation of any vapors. General dilution and/or local exhoust ventilation in volume to keep PEL/TLV of most hazardous ingredient below acceptable limit and lel below stated limit.

Individual protection measures:

Respiratory protection: None under normal use. Avoid breathing vapors. In restricted areas, use approved chemical/mechanical filters designed to remove a combination or particles and vapor. In confined areas, use an approved air line respirator or hood. Self-contained breathing apparatus is required for vapor concentrations above PEL/TLV limits.

Protective gloves: None under normal use. Use solvent-resistant for prolonged or repeated contact.

Eye protection: None under normal use. However, use of safety glasses with splah guards or full face shield should be used if indicated.

Other protective clothing or equipment: None under normal use. However, use of solvent- resitant aprons or other clothing is recommended. Eye washes and safety showers in the workplace are recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Aerosol product

Vapor Pressure: Not determined

Vapor Density: Heavier than air

Freezing point: Not determined

Density: 0.734053342

Boiling point: N/A

Evaporation rate: Slower than ether

Explosive Limits: Not applicable

Autoignition temperature: Not determined

Viscosity: Not determined

Odor: Oil

Odor threshold: Not determined

pH: Not applicable

Melting point: Not determined

Solubility: Not determined

Flash point: None

Flammability: Level 3 Aerosol

Partition coefficient (n- Not determined

octanol/water):

Decomposition temperature: Not determined

10. STABILITY AND REACTIVITY

Reactivity: Not reactive under normal conditions of use.

Chemical stability: Stable under normal storage and handling conditions.

Possibility of hazardous reactions: None known.

Incompatible materials:

No data

Hazardous decomposition products:

No data

11. TOXICOLOGICAL INFORMATION

Long-term toxicological studies have not been conducted for this product.

12. ECOLOGICAL INFORMATION

Long-term ecological studies have not been conducted for this product.

13. DISPOSAL CONSIDERATIONS

Dispose of in accordance with local, state, and federal regulations. Before attempting clean up, refer to other sections of this document for hazard cautionary information.

14. TRANSPORT INFORMATION

By land: DOT Proper Shipping Name: None required per 49 CFR 173.306(i) for products that conform to the Limited Quantity provisions. Commodity shipping description: Lubricant, NOI

By water: DOT & IMDG Proper Shipping Name: UN1950, Aerosols, 2.1, LTD QTY

By air: DOT & IATA Proper Shipping Name: UN1950, Aerosols, flammable, 2.1, LTD QTY (packing instruction Y203 applies)

15. REGULATORY INFORMATION

All ingredients are either listed on the TSCA inventory or are exempt.

16. OTHER INFORMATION

Date revised: 2015-05-18 Revision 0

Date Printed: 2015-05-18

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED ACCURATE. HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THE DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF. BECAUSE THE INFORMATION CONTAINED HEREIN MAY BE APPLIED UNDER CONDITIONS BEYOND OUR CONTROL, WE ASSUME NO RESPONSIBILITY FOR ITS USE.

AIMITET-CC Page 4 of 4