

Ultimate Carpet Clean With PTEF
Safety Data Sheet
According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations
Revision Date: 04/14/2015 Date of issue: 04/14/2015

Version: 1.0

SECTION 1: IDENTIFICATION

Product Identifier Product Form: Mixture

Product Name: Ultimate Carpet Clean With PTEF

Product Code: 889XX

Intended Use of the Product

Cleaner

Name, Address, and Telephone of the Responsible Party

Company Star brite Inc. 4041 SW 47th Avenue

Fort Lauderdale, FL 33314

(954)587-6280

www.starbrite.com

Emergency Telephone Number

Emergency Number : US: (800) 424-9300; International: (703) 527-3887

SECTION 2: HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

Classification (GHS-US) Eye Dam. 1 H318

Full text of H-phrases: see section 16

Label Elements GHS-US Labeling

Hazard Pictograms (GHS-US)



Signal Word (GHS-US) : Danger

Hazard Statements (GHS-US) : H318 - Causes serious eye damage.

: P280 - Wear protective gloves, protective clothing, and eye protection. **Precautionary Statements (GHS-US)**

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P310 - Immediately call a poison center or doctor.

P501 - Dispose of contents/container in accordance with local, regional, national, and

international regulations.

Other Hazards

Exposure may aggravate those with pre-existing eye, skin, or respiratory conditions.

Unknown Acute Toxicity (GHS-US) Not available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

Name	Product Identifier	% (w/w)	Classification (GHS-US)
Benzenesulfonic acid, 2,4-dimethyl-, sodium	(CAS No) 827-21-4	5 - 8	Acute Tox. 4 (Oral), H302
salt			Skin Irrit. 2, H315
			Eye Irrit. 2A, H319
Alcohols, C9-11, ethoxylated	(CAS No) 68439-46-3	2 - 4	Acute Tox. 4 (Oral), H302
-			Eye Dam. 1, H318
Diethylene glycol monobutyl ether	(CAS No) 112-34-5	2 - 3	Flam. Liq. 4, H227
			Eye Irrit. 2A, H319

04/14/2015 RTATEP-CC EN (English US) 1/12

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Tetrapotassium pyrophosphate	(CAS No) 7320-34-5	2 - 3	Eye Irrit. 2A, H319
Sulfonic acids, C14-16-alkane hydroxy and	(CAS No) 68439-57-6	1 - 2	Skin Irrit. 2, H315
C14-16-alkene, sodium salts			Eye Dam. 1, H318
			Aquatic Acute 2, H401
Petroleum distillates, hydrotreated light	(CAS No) 64742-47-8	0.1 - 1	Flam. Liq. 3, H226
			Skin Irrit. 2, H315
			STOT SE 3, H336
			Asp. Tox. 1, H304
			Aquatic Acute 2, H401
			Aquatic Chronic 2, H411
n-Amyl acetate	(CAS No) 628-63-7	< 0.1	Flam. Liq. 3, H226
Isopropyl alcohol	(CAS No) 67-63-0	< 0.1	Flam. Liq. 2, H225
			Eye Irrit. 2A, H319
			STOT SE 3, H336

Full text of H-phrases: see section 16

*The specific chemical identity and/or exact percentage of composition has been withheld as a trade secret within the meaning of the OSHA Hazard Communication Standard [29 CFR 1910.1200]. A range of concentration as prescribed by Controlled Products Regulations has been used where necessary, due to varying composition.

SECTION 4: FIRST AID MEASURES

Description of First Aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

Inhalation: When symptoms occur: go into open air and ventilate suspected area. Call a POISON CENTER or doctor/physician if you feel unwell.

Skin Contact: Remove contaminated clothing. Drench affected area with water for at least 15 minutes. Obtain medical attention if irritation develops or persists.

Eye Contact: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing for at least 60 minutes. Immediately call a POISON CENTER or doctor/physician.

Ingestion: Rinse mouth. Do NOT induce vomiting. Call a POISON CENTER/doctor/physician if you feel unwell.

Most Important Symptoms and Effects Both Acute and Delayed

General: Causes serious eye damage.

Inhalation: May cause irritation to the respiratory tract.

Skin Contact: May cause mild skin irritation.

Eye Contact: Causes serious eye damage. Causes permanent damage to the cornea, iris, or conjunctiva.

Ingestion: Ingestion is likely to be harmful or have adverse effects.

Chronic Symptoms: None known.

Indication of Any Immediate Medical Attention and Special Treatment Needed

If you feel unwell, seek medical advice (show the label where possible).

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media: Dry powder, alcohol-resistant foam, water in large amounts, carbon dioxide (CO₂).

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire. Burning liquid may float on water.

Special Hazards Arising From the Substance or Mixture

Fire Hazard: Product is not flammable, but may burn at high temperatures.

Explosion Hazard: Product is not explosive.

Reactivity: Hazardous reactions will not occur under normal conditions.

Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Use water spray or fog for cooling exposed containers. In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion. Do not breathe fumes from fires or vapors from decomposition. Do not allow run-off from firefighting to enter drains or water courses.

04/14/2015 RTATEP-CC EN (English US) 2/12

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection. **Hazardous Combustion Products:** Carbon oxides (CO, CO₂).

Reference to Other Sections

Refer to section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Avoid all unnecessary exposure.

For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Evacuate unnecessary personnel. Eliminate ignition sources. Stop leak if safe to do so. Ventilate area.

Environmental Precautions

Prevent entry to sewers and public waters.

Methods and Material for Containment and Cleaning Up

For Containment: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Methods for Cleaning Up: Clear up spills immediately and dispose of waste safely. Absorb and/or contain spill with inert material, then place in suitable container. Do not take up in combustible material such as: saw dust or cellulosic material. Contact competent authorities after a spill.

Reference to Other Sections

See heading 8, Exposure Controls and Personal Protection. Concerning disposal elimination after cleaning, see item 13.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Additional Hazards When Processed: Do not get in eyes, on skin, or on clothing. Do not breathe vapor or mist. Use appropriate personal protection equipment (PPE).

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work. Do not eat, drink or smoke when using this product. Wash hands and forearms thoroughly after handling.

Conditions for Safe Storage, Including Any Incompatibilities

Storage Conditions: Store in a dry, cool and well-ventilated place. Keep container closed when not in use. Keep cool. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials.

Incompatible Materials: Strong acids. Strong bases. Strong oxidizers. Alkaline products. Halogens.

Specific End Use(s) Cleaner

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

For substances listed in section 3 that are not listed here, there are no established Exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), NIOSH (REL), OSHA (PEL), Canadian provincial governments, or the Mexican government

the mexican government			
Diethylene glycol monobutyl ether (112-34-5)			
USA ACGIH	ACGIH TWA (ppm)	10 ppm (inhalable fraction and vapor)	
Manitoba	OEL TWA (ppm)	10 ppm (inhalable fraction and vapor)	
Newfoundland & Labrador	OEL TWA (ppm)	10 ppm (inhalable fraction and vapor)	
Nova Scotia	OEL TWA (ppm)	10 ppm (inhalable fraction and vapor)	
Prince Edward Island	OEL TWA (ppm)	10 ppm (inhalable fraction and vapor)	
Petroleum distillates, hydro	Petroleum distillates, hydrotreated light (64742-47-8)		
British Columbia	OELTWA (mg/m³)	200 mg/m³ (application restricted to conditions in which	
	-	there are negligible aerosol exposures)	
n-Amyl acetate (628-63-7)	n-Amyl acetate (628-63-7)		
USA ACGIH	ACGIH TWA (ppm)	50 ppm	
USA ACGIH	ACGIH STEL (ppm)	100 ppm	

04/14/2015 RTATEP-CC EN (English US) 3/12

Safety Data Sheet According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

USA OSHA	OSHA PEL (TWA) (mg/m³)	525 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	100 ppm
USA NIOSH	NIOSH REL (TWA) (mg/m³)	525 mg/m ³
USA NIOSH	NIOSH REL (TWA) (ppm)	100 ррт
USA IDLH	US IDLH (ppm)	1000 ppm
Alberta	OEL STEL (mg/m³)	532 mg/m ³
Alberta	OEL STEL (ppm)	100 ppm
Alberta	OELTWA (mg/m³)	266 mg/m ³
Alberta	OELTWA (ppm)	50 ppm
British Columbia	OEL STEL (ppm)	100 ppm
British Columbia	OEL TWA (ppm)	50 ppm
Manitoba	OEL STEL (ppm)	100 ppm
Manitoba	OEL TWA (ppm)	50 ppm
New Brunswick	OELTWA (mg/m³)	532 mg/m ³
New Brunswick	OEL TWA (ppm)	100 ppm
Newfoundland & Labrador	OEL STEL (ppm)	100 ppm
Newfoundland & Labrador	OELTWA (ppm)	50 ppm
Nova Scotia	OEL STEL (ppm)	100 ppm
Nova Scotia	OELTWA (ppm)	50 ppm
Nunavut	OEL STEL (mg/m³)	800 mg/m ³
Nunavut	OEL STEL (ppm)	150 ppm
Nunavut	OEL TWA (mg/m³)	530 mg/m ³
Nunavut	OEL TWA (ppm)	100 ppm
Northwest Territories	OEL STEL (mg/m³)	800 mg/m ³
Northwest Territories	OEL STEL (ppm)	150 ppm
Northwest Territories	OEL TWA (mg/m³)	530 mg/m ³
Northwest Territories	OEL TWA (ppm)	100 ppm
Ontario	OEL STEL (ppm)	100 ppm
Ontario	OEL TWA (ppm)	50 ppm
Prince Edward Island	OEL STEL (ppm)	100 ppm
Prince Edward Island	OEL TWA (ppm)	50 ppm
Québec	VECD (mg/m³)	532 mg/m ³
Québec	VECD (ppm)	100 ppm
Québec	VEMP (mg/m³)	266 mg/m ³
Québec	VEMP (ppm)	50 ppm
Saskatchewan	OEL STEL (ppm)	100 ppm
Saskatchewan	OELTWA (ppm)	50 ppm
Yukon	OEL STEL (mg/m³)	780 mg/m ³
Yukon	OEL STEL (ppm)	150 ppm
Yukon	OELTWA (mg/m³)	525 mg/m ³
Yukon	OELTWA (ppm)	100 ppm
kopropyl alcohol (67-63-0)		
USA ACGIH	ACGIH TWA (ppm)	200 ppm
USA ACGIH	ACGIH STEL (ppm)	400 ppm
USA ACGIH	ACGIH chemical category	Not Classifiable as a Human Carcinogen
USA OSHA	OSHA PEL (TWA) (mg/m³)	980 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	400 ppm
USA NIOSH	NIOSH REL (TWA) (mg/m³)	980 mg/m ³
USA NIOSH	NIOSH REL (TWA) (ppm)	400 ppm
USA NIOSH	NIOSH REL (STEL) (mg/m³)	1225 mg/m³
USA NIOSH	NIOSH REL (STEL) (ppm)	500 ppm

04/14/2015 RTATEP-CC EN (English US) 4/12

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

USA IDIH	US IDLH (ppm)	2000 ppm (10% LEL)
Alberta	OEL STEL (mg/m³)	984 mg/m ³
Alberta	OEL STEL (ppm)	400 ppm
Alberta	OEL TWA (mg/m³)	492 mg/m ³
Alberta	OELTWA (ppm)	200 ppm
British Columbia	OEL STEL (ppm)	400 ppm
British Columbia	OELTWA (ppm)	200 ppm
Manitoba	OEL STEL (ppm)	400 ppm
Manitoba	OELTWA (ppm)	200 ppm
New Brunswick	OEL STEL (mg/m³)	1230 mg/m ³
New Brunswick	OEL STEL (ppm)	500 ppm
New Brunswick	OELTWA (mg/m³)	983 mg/m ³
New Brunswick	OELTWA (ppm)	400 ppm
Newfoundland & Labrador	OEL STEL (ppm)	400 ppm
Newfoundland & Labrador	OELTWA (ppm)	200 ppm
Nova Scotia	OEL STEL (ppm)	400 ppm
Nova Scotia	OELTWA (ppm)	200 ppm
Nunavut	OEL STEL (mg/m³)	1228 mg/m ³
Nunavut	OEL STEL (ppm)	500 ppm
Nunavut	OEL TWA (mg/m³)	983 mg/m³
Nunavut	OEL TWA (ppm)	400 ppm
Northwest Territories	OEL STEL (mg/m³)	1228 mg/m ³
Northwest Territories	OEL STEL (ppm)	500 ppm
Northwest Territories	OELTWA (mg/m³)	983 mg/m³
Northwest Territories	OELTWA (ppm)	400 ppm
Ontario	OEL STEL (ppm)	400 ppm
Ontario	OEL TWA (ppm)	200 ppm
Prince Edward Island	OEL STEL (ppm)	400 ppm
Prince Edward Island	OEL TWA (ppm)	200 ppm
Québec	VECD (mg/m³)	1230 mg/m ³
Québec	VECD (ppm)	500 ppm
Québec	VEMP (mg/m³)	985 mg/m ³
Québec	VEMP (ppm)	400 ppm
Saskatchewan	OEL STEL (ppm)	400 ppm
Saskatchewan	OEL TWA (ppm)	200 ppm
Yukon	OEL STEL (mg/m³)	1225 mg/m³
Yukon	OEL STEL (ppm)	500 ppm
Yukon	OEL TWA (mg/m³)	980 mg/m ³
Yukon	OELTWA (ppm)	400 ppm

Exposure Controls

Appropriate Engineering Controls: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed

Personal Protective Equipment: Protective goggles. Gloves. Protective clothing. Insufficient ventilation: wear respiratory protection.









Materials for Protective Clothing: Chemically resistant materials and fabrics.

Hand Protection: Wear chemically resistant protective gloves.

Eye Protection: Chemical safety goggles.

Skin and Body Protection: Wear appropriate personal protective equipment.

04/14/2015 RTATEP-CC EN (English US) 5/12

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Respiratory Protection: If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. **Other Information:** When using, do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

<u>Information on Basic Physical and Chemical Properties</u>

Physical State : Liquid

Appearance: Colorless LiquidOdor: CharacteristicOdor Threshold: Not available

PH : 10.45

Evaporation Rate Not available **Melting Point** Not available **Freezing Point** Not available **Boiling Point** 100 °C (212 °F) **Flash Point** Not flammable **Auto-ignition Temperature** Not available **Decomposition Temperature** Not available Flammability (solid, gas) Not available Not available **Lower Flammable Limit Upper Flammable Limit** Not available **Vapor Pressure** Not available Not available Relative Vapor Density at 20 °C **Relative Density** Not available

Specific Gravity : 1.023

Solubility: Soluble in waterPartition Coefficient: N-Octanol/Water: Not availableViscosity: Not available

Explosion Data – Sensitivity to Mechanical Impact: Not expected to present an explosion hazard due to mechanical impact.

Explosion Data – Sensitivity to Static Discharge : Static discharge could act as an ignition source.

SECTION 10: STABILITY AND REACTIVITY

Reactivity: Hazardous reactions will not occur under normal conditions.

Chemical Stability: Stable under normal conditions.

Possibility of Hazardous Reactions: Hazardous polymerization will not occur.

<u>Conditions to Avoid</u>: Direct sunlight. Extremely high or low temperatures. Sparks, heat, open flame and other sources of ignition. Incompatible materials.

Incompatible Materials: Strong acids. Strong bases. Strong oxidizers. Alkaline substances. Halogens.

<u>Hazardous Decomposition Products</u>: Thermal decomposition generates : Carbon oxides (CO, CO₂). Sodium oxides. Nitrogen oxides. Sulfur oxides.

SECTION 11: TOXICOLOGICAL INFORMATION

Information on Toxicological Effects - Product

Acute Toxicity: Not classified ID50 and IC50 Data: Not available Skin Corrosion/Irritation: Not classified

pH: 10.45

Serious Eye Damage/Irritation: Causes serious eye damage.

pH: 10.45

Respiratory or Skin Sensitization: Not classified

Germ Cell Mutagenicity: Not classified

Teratogenicity: Not classified **Carcinogenicity:** Not classified

Specific Target Organ Toxicity (Repeated Exposure): Not classified

04/14/2015 RTATEP-CC EN (English US) 6/12

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): Not classified

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: May cause irritation to the respiratory tract.

Symptoms/Injuries After Skin Contact: May cause mild skin irritation.

Symptoms/Injuries After Eye Contact: Causes serious eye damage. Causes permanent damage to the cornea, iris, or conjunctiva.

Symptoms/Injuries After Ingestion: Ingestion is likely to be harmful or have adverse effects.

Chronic Symptoms: None known.

Information on Toxicological Effects - Ingredient(s)

ID50 and IC50 Data:

Benzenesulfonic acid, 2,4-dimethyl-, sodium salt (827-21-4)		
ATE US (oral)	500.00 mg/kg body weight	
Alcohols, C9-11, ethoxylated (68439-46-3)		
ID50 Oral Rat	1400 mg/kg	
ID50 Dermal Rat	> 2 g/kg	
Sulfonic acids, C14-16-alkane hydroxy and C14-16-alkene, so	dium salts (68439-57-6)	
ID50 Oral Rat	2310 mg/kg	
ID50 Dermal Rabbit	6300 mg/kg	
Diethylene glycol monobutyl ether (112-34-5)		
ID50 Oral Rat	3384 mg/kg	
ID50 Dermal Rabbit	2700 mg/kg	
Tetrapotassium pyrophosphate (7320-34-5)		
ID50 Dermal Rabbit	> 2000 mg/kg	
Petroleum distillates, hydrotreated light (64742-47-8)		
ID50 Oral Rat	> 5000 mg/kg	
ID50 Dermal Rabbit	> 2000 mg/kg	
IC50 Inhalation Rat	> 5.2 mg/l/4h	
kopropyl alcohol (67-63-0)		
ID50 Oral Rat	4710 mg/kg	
ID50 Dermal Rabbit	4059 mg/kg	
IC50 Inhalation Rat	72600 mg/m³ (Exposure time: 4 h)	
Isopropyl alcohol (67-63-0)		
IARC Group	3	

SECTION 12: ECOLOGICAL INFORMATION

Toxicity No additional information available

TOAKKY TO GUURONII INOTHIUDE		
Sulfonic acids, C14-16-alkane hydroxy and C14-16-alkene, sodium salts (68439-57-6)		
IC50 Fish 1	4.2 mg/l (Exposure time: 96 h - Species: Brachydanio rerio [static])	
EC50 Daphnia 1	4.53 mg/l (Ceriodaphnia sp)	
IC 50 Fish 2	12.2 mg/l (Exposure time: 96 h - Species: Brachydanio rerio [semi-static])	
ErC50 (algae)	5.2 mg/l (Water quality - Marine Algal Growth Inhibition Test with Skeletonema costatum	
_	and Phaeodactylum tricornutum)	
Diethylene glycol monobutyl ether (112-34-5)		
IC50 Fish 1	1300 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])	
EC50 Daphnia 1	> 100 mg/l (Exposure time: 48 h - Species: Daphnia magna)	
Tetrapotassium pyrophosphate (7320-34-5)		
IC50 Fish 1	101 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)	
EC50 Daphnia 1	101 mg/l (Exposure time: 48 h - Species: water flea)	
Petroleum distillates, hydrotreated light	t (64742-47-8)	
IC50 Fish 1	45 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])	

04/14/2015 RTATEP-CC EN (English US) 7/12

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

	<u> </u>	
IC 50 Fish 2	2.2 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])	
n-Amyl acetate (628-63-7)		
LC50 Fish 1	650 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])	
Isopropyl alcohol (67-63-0)		
IC50 Fish 1	9640 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])	
EC50 Daphnia 1	13299 mg/l (Exposure time: 48 h - Species: Daphnia magna)	
EC50 Other Aquatic Organisms 1	1000 mg/l (Exposure time: 96 h - Species: Desmodesmus subspicatus)	
IC 50 Fish 2	11130 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])	
EC50 Other Aquatic Organisms 2	1000 mg/l (Exposure time: 72 h - Species: Desmodesmus subspicatus)	
Persistence and Degradability		

Ultimate Carpet Clean With PTEF	
Persistence and Degradability	Not established.

Bioaccumulative Potential

Ultimate Carpet Clean With PTEF		
Bioaccumulative Potential	Not established.	
Diethylene glycol monobutyl ether (112-34-5)		
BCF Fish 1	3CF Fish 1 (no bioconcentration expected)	
Petroleum distillates, hydrotreated light (64742-47-8)		
BCF Fish 1 61 - 159		
kopropyl alcohol (67-63-0)		
Log Pow	0.05 (at 25 °C)	

Mobility in Soil Not available

Other Adverse Effects

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Recommendations: Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations.

Additional Information: Handle empty containers with care because residual vapors are flammable.

SECTION 14: TRANSPORT INFORMATION

In Accordance With ICAO/IATA/DOT/TDG/IMDG

UN Number Not regulated for transport.

UN Proper Shipping Name Not regulated for transport.

Transport Hazard Class(es) Not regulated for transport.

Additional Information Not available

Marine Pollutant: No

Transport by sea Not regulated for transport.

Air transport Not regulated for transport.

SECTION 15: REGULATORY INFORMATION

US Federal Regulations

Ultimate Carpet Clean With PTEF		
SARA Section 311/312 Hazard Classes Immediate (acute) health hazard		
Benzenesulfonic acid, 2,4-dimethyl-, sodium salt (827-21-4)		
Listed on the United States TSCA (Toxic Substances Control Act)	inventory	
Alcohols, C9-11, ethoxylated (68439-46-3)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
Sulfonic acids, C14-16-alkane hydroxy and C14-16-alkene, sodium salts (68439-57-6)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
Diethylene glycol monobutyl ether (112-34-5)		
Listed on the United States TSCA (Toxic Substances Control Act	Listed on the United States TSCA (Toxic Substances Control Act) inventory	

04/14/2015 RTATEP-CC 8/12 EN (English US)

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test
	rule under TSCA.
	Y2 - Y2 - indicates an exempt polymer that is a polyester and is
	made only from reactants included in a specified list of low concern
	reactants that comprises one of the eligibility criteria for the
	exemption rule.
Tetrapotassium pyrophosphate (7320-34-5)	
Listed on the United States TSCA (Toxic Substances	Control Act) inventory
Petroleum distillates, hydrotreated light (64742-4	7-8)
Listed on the United States TSCA (Toxic Substances	Control Act) inventory
SARA Section 311/312 Hazard Classes	Fire hazard
	Immediate (acute) health hazard
n-Amyl acetate (628-63-7)	
Listed on the United States TSCA (Toxic Substances	Control Act) inventory
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test
	rule under TSCA.
kopropyl alcohol (67-63-0)	
Listed on the United States TSCA (Toxic Substances	Control Act) inventory
Listed on United States SARA Section 313	
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test
- · · ·	rule under TSCA.
SARA Section 313 - Emission Reporting	1.0 % (only if manufactured by the strong acid process, no supplier
- 0	notification)

_
Alcohols, C9-11, ethoxylated (68439-46-3)
U.S Texas - Effects Screening Levels - Long Term
U.S Texas - Effects Screening Levels - Short Term

Sulfonic acids, C14-16-alkane hydroxy and C14-16-alkene, sodium salts (68439-57-6)

- U.S. Texas Effects Screening Levels Long Term
- U.S. Texas Effects Screening Levels Short Term

Diethylene glycol monobutyl ether (112-34-5)

- U.S. Texas Effects Screening Levels Long Term
- U.S. Texas Effects Screening Levels Short Term

Tetrapotassium pyrophosphate (7320-34-5)

- U.S. Texas Effects Screening Levels Long Term
- U.S. Texas Effects Screening Levels Short Term

Petroleum distillates, hydrotreated light (64742-47-8)

- U.S. New Hampshire Regulated Toxic Air Pollutants Ambient Air Levels (AALs) 24-Hour
- U.S. New Hampshire Regulated Toxic Air Pollutants Ambient Air Levels (AALs) Annual
- U.S. Texas Effects Screening Levels Long Term
- U.S. Texas Effects Screening Levels Short Term

n-Amyl acetate (628-63-7)

- U.S. Connecticut Hazardous Air Pollutants HLVs (30 min)
- U.S. Connecticut Hazardous Air Pollutants HLVs (8 hr)
- U.S. Delaware Pollutant Discharge Requirements Reportable Quantities
- U.S. Idaho Non-Carcinogenic Toxic Air Pollutants Acceptable Ambient Concentrations
- U.S. Idaho Non-Carcinogenic Toxic Air Pollutants Emission Levels (ELs)
- U.S. Idaho Occupational Exposure Limits TWAs
- U.S. Louisiana Reportable Quantity List for Pollutants
- U.S. Massachusetts Oil & Hazardous Material List Groundwater Reportable Concentration Reporting Category 1
- U.S. Massachusetts Oil & Hazardous Material List Groundwater Reportable Concentration Reporting Category 2

04/14/2015 RTATEP-CC EN (English US) 9/12

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

- U.S. Massachusetts Oil & Hazardous Material List Reportable Quantity
- U.S. Massachusetts Oil & Hazardous Material List Soil Reportable Concentration Reporting Category 1
- U.S. Massachusetts Oil & Hazardous Material List Soil Reportable Concentration Reporting Category 2
- RTK U.S. Massachusetts Right To Know List
- U.S. Michigan Occupational Exposure Limits TWAs
- U.S. Michigan Polluting Materials List
- U.S. Minnesota Hazardous Substance List
- U.S. Minnesota Permissible Exposure Limits TWAs
- U.S. New Jersey Discharge Prevention List of Hazardous Substances
- RTK U.S. New Jersey Right to Know Hazardous Substance List
- U.S. New Jersey Special Health Hazards Substances List
- U.S. New York Occupational Exposure Limits TWAs
- U.S. New York Reporting of Releases Part 597 List of Hazardous Substances
- U.S. North Dakota Air Pollutants Guideline Concentrations 1-Hour
- U.S. North Dakota Air Pollutants Guideline Concentrations 8-Hour
- U.S. Oregon Permissible Exposure Limits TWAs
- RTK U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- RTK U.S. Pennsylvania RTK (Right to Know) List
- U.S. Tennessee Occupational Exposure Limits TWAs
- U.S. Texas City of Austin Aerosol Paint and Glue Restrictions
- U.S. Texas Effects Screening Levels Long Term
- U.S. Texas Effects Screening Levels Short Term
- U.S. Vermont Permissible Exposure Limits TWAs
- U.S. Washington Permissible Exposure Limits STELs
- U.S. Washington Permissible Exposure Limits TWAs
- U.S. Wisconsin Hazardous Air Contaminants All Sources Emissions From Stack Heights 25 Feet to Less Than 40 Feet
- U.S. Wisconsin Hazardous Air Contaminants All Sources Emissions From Stack Heights 40 Feet to Less Than 75 Feet
- U.S. Wisconsin Hazardous Air Contaminants All Sources Emissions From Stack Heights 75 Feet or Greater
- U.S. Wisconsin Hazardous Air Contaminants All Sources Emissions From Stack Heights Less Than 25 Feet

Isopropyl alcohol (67-63-0)

- U.S. California SCAQMD Toxic Air Contaminants Non-Cancer Acute
- U.S. California SCAQMD Toxic Air Contaminants Non-Cancer Chronic
- U.S. California Toxic Air Contaminant List (AB 1807, AB 2728)
- U.S. Connecticut Hazardous Air Pollutants HLVs (30 min)
- U.S. Connecticut Hazardous Air Pollutants HLVs (8 hr)
- **U.S. Connecticut Volatile Substances**
- U.S. Idaho Non-Carcinogenic Toxic Air Pollutants Acceptable Ambient Concentrations
- U.S. Idaho Non-Carcinogenic Toxic Air Pollutants Emission Levels (ELs)
- U.S. Idaho Occupational Exposure Limits TWAs
- RTK U.S. Massachusetts Right To Know List
- U.S. Massachusetts Toxics Use Reduction Act
- U.S. Michigan Occupational Exposure Limits STELs
- U.S. Michigan Occupational Exposure Limits TWAs
- U.S. Minnesota Hazardous Substance List
- U.S. Minnesota Permissible Exposure Limits STELs
- U.S. Minnesota Permissible Exposure Limits TWAs
- U.S. New Hampshire Regulated Toxic Air Pollutants Ambient Air Levels (AALs) 24-Hour
- U.S. New Hampshire Regulated Toxic Air Pollutants Ambient Air Levels (AAIs) Annual
- U.S. New Jersey Discharge Prevention List of Hazardous Substances
- U.S. New Jersey Environmental Hazardous Substances List
- RTK U.S. New Jersey Right to Know Hazardous Substance List
- U.S. New Jersey Special Health Hazards Substances List
- U.S. New York Occupational Exposure Limits TWAs

04/14/2015 RTATEP-CC EN (English US) 10/12

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 1-Hour

U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 8-Hour

U.S. - Oregon - Permissible Exposure Limits - TWAs

RTK - U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

RTK - U.S. - Pennsylvania - RTK (Right to Know) List

U.S. - Rhode Island - Air Toxics - Acceptable Ambient Levels - 1-Hour

U.S. - Tennessee - Occupational Exposure Limits - STELs

U.S. - Tennessee - Occupational Exposure Limits - TWAs

U.S. - Texas - City of Austin - Aerosol Paint and Glue Restrictions

U.S. - Texas - Effects Screening Levels - Long Term

U.S. - Texas - Effects Screening Levels - Short Term

U.S. - Vermont - Permissible Exposure Limits - STELs

U.S. - Vermont - Permissible Exposure Limits - TWAs

U.S. - Washington - Permissible Exposure Limits - STELs

U.S. - Washington - Permissible Exposure Limits - TWAs

Canadian Regulations

Ultimate Carpet Clean With PTEF			
WHMIS Classification	Class E - Corrosive Material		
	nethyl-, sodium salt (827-21-4)		
Listed on the Canadian NDSL (Non-Domestic Substances List)			
WHMIS Classification	Class D Division 1 Subdivision B - Toxic material causing immediate and serious toxic effects		
	Class D Division 2 Subdivision B - Toxic material causing other toxic effects		
Alcohols, C9-11, ethoxylated			
Listed on the Canadian DSL (D	,		
WHMIS Classification	Class E - Corrosive Material		
Sulfonic acids, C14-16-alkane hydroxy and C14-16-alkene, sodium salts (68439-57-6)			
Listed on the Canadian DSL (Domestic Substances List)			
WHMIS Classification	Class E - Corrosive Material		
	Class D Division 2 Subdivision B - Toxic material causing other toxic effects		
Diethylene glycol monobutyl			
Listed on the Canadian DSL (Domestic Substances List)			
IDL Concentration 1 %			
WHMIS Classification	Class B Division 3 - Combustible Liquid		
	Class D Division 2 Subdivision B - Toxic material causing other toxic effects		
Tetrapotassium pyrophosphate (7320-34-5)			
Listed on the Canadian DSL (D	,		
WHMIS Classification	Class D Division 2 Subdivision B - Toxic material causing other toxic effects		
Petroleum distillates, hydroti	reated light (64742-47-8)		
Listed on the Canadian DSL (D	omestic Substances List)		
WHMIS Classification	Class B Division 3 - Combustible Liquid		
	Class D Division 2 Subdivision B - Toxic material causing other toxic effects		
n-Amyl acetate (628-63-7)			
Listed on the Canadian DSL (D			
Listed on the Canadian IDL (In	gredient Disclosure List)		
IDL Concentration 1 %			
WHMIS Classification	Class B Division 2 - Flammable Liquid		

04/14/2015 RTATEP-CC EN (English US) 11/12

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

kopropyl alcohol (67-63-0)			
Listed on the Canadian DSL (D	n the Canadian DSL (Domestic Substances List)		
Listed on the Canadian IDL (In	ed on the Canadian IDL (Ingredient Disclosure List)		
IDL Concentration 1 %	DL Concentration 1 %		
WHMIS Classification	Class B Division 2 - Flammable Liquid		
	Class D Division 2 Subdivision B - Toxic material causing other toxic effects		

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.

Revision Date : 04/14/2015

Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA

Hazard Communication Standard 29 CFR 1910.1200.

GHS Full Text Phrases:

Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Aquatic Acute 2	Hazardous to the aquatic environment - Acute Hazard Category 2
Aquatic Chronic 2	Hazardous to the aquatic environment - Chronic Hazard Category 2
Asp. Tox. 1	Aspiration hazard Category 1
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Liq. 2	Flammable liquids Category 2
Flam. Liq. 3	Flammable liquids Category 3
Flam. Liq. 4	Flammable liquids Category 4
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H227	Combustible liquid
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H318	Causes serious eye damage
Н319	Causes serious eye irritation
Н336	May cause drowsiness or dizziness
H401	Toxic to aquatic life
H411	Toxic to aquatic life with long lasting effects

NFPA Health Hazard : 3 - Short exposure could cause serious temporary or

residual injury even though prompt medical attention was

given.


NFPA Fire Hazard : 1 - Must be preheated before ignition can occur.

NFPA Reactivity : 0 - Normally stable, even under fire exposure conditions,

and are not reactive with water.

Party Responsible for the Preparation of This Document

Star brite Inc. (954)587-6280



North America GHS US 2012 & WHMIS 2

04/14/2015 RTATEP-CC EN (English US) 12/12