

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Revision Date: 08/06/2015 Date of issue: 08/06/2015 Version: 1.0

SECTION 1: IDENTIFICATION

Product Identifier Product Form: Mixture

Product Name: POWER PINE WASH & WAX

Product Code: 947XX

Intended Use of the Product

Cleaner

Name, Address, and Telephone of the Responsible Party

Company Star brite Inc.

4041 SW 47th Avenue Fort Lauderdale, FL 33314

(954)587-6280 www.starbrite.com

Emergency Telephone Number

Emergency Number: US: (800) 424-9300; International: (703) 527-3887 (CHEMTREC)

SECTION 2: HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

Classification (GHS-US)

Skin Irrit. 2 H315 Eve Dam. 1 H318 Skin Sens. 1 H317 Carc. 2 H351

H335 STOT SE 3

Full text of H-phrases: see section 16

Label Elements GHS-US Labeling

Hazard Pictograms (GHS-US)







Signal Word (GHS-US)

: Danger

Hazard Statements (GHS-US) : H315 - Causes skin irritation.

> H317 - May cause an allergic skin reaction. H318 - Causes serious eve damage. H335 - May cause respiratory irritation.

H351 - Suspected of causing cancer.

Precautionary Statements (GHS-US): P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.

P261 - Avoid breathing vapors, mist, or spray.

P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.

P271 - Use only outdoors or in a well-ventilated area.

P272 - Contaminated work clothing must not be allowed out of the workplace.

P280 - Wear protective gloves, protective clothing, and eye protection.

P302+P352 - If on skin: Wash with plenty of water.

P304+P340 - If inhaled: Remove person to fresh air and keep at rest in a position

comfortable for breathing.

P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

08/06/2015 EOTT.B-CC EN (English US) 1/12

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

P308+P313 - If exposed or concerned: Get medical advice/attention.

P310 - Immediately call a poison center or doctor.

P321 - Specific treatment (see section 4 on this SDS).

P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.

P362+P364 - Take off contaminated clothing and wash it before reuse.

P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

P405 - Store locked up.

P501 - Dispose of contents/container in accordance with local, regional, national, and international regulations.

Other Hazards

Exposure may aggravate those with pre-existing eye, skin, or respiratory conditions.

Aquatic Acute 3 H402

Aquatic Chronic 3 H412

H402 - Harmful to aquatic life.

H412 - Harmful to aquatic life with long lasting effects.

P273 - Avoid release to the environment.

Unknown Acute Toxicity (GHS-US) Not available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

Name	Product Identifier	% (w/w)	Classification (GHS-US)
Sodium lauryl sulfate	(CAS No) 151-21-3	10 - 18	Flam. Sol. 2, H228
			Acute Tox. 4 (Oral), H302
			Acute Tox. 3 (Dermal), H311
			Acute Tox. 4 (Inhalation:dust,mist), H332
			Skin Irrit. 2, H315
			Eye Dam. 1, H318
			STOT SE 3, H335
			Aquatic Acute 2, H401
			Aquatic Chronic 3, H412
Dodecanamide, N,N-bis(2-hydroxyethyl)-	(CAS No) 120-40-1	1 - 5	Skin Irrit. 2, H315
			Eye Dam. 1, H318
			Aquatic Chronic 2, H411
Pine oil	(CAS No) 8002-09-3	1 - 3.5	Flam. Liq. 3, H226
			Skin Irrit. 2, H315
			Eye Irrit. 2A, H319
			Skin Sens. 1, H317
			STOT SE 3, H335
			Asp. Tox. 1, H304
			Aquatic Acute 3, H402
Sulfonic acids, C14-16-alkane hydroxy and	(CAS No) 68439-57-6	1 - 2.5	Skin Irrit. 2, H315
C14-16-alkene, sodium salts			Eye Dam. 1, H318
			Aquatic Acute 2, H401
Poly(oxy-1,2-ethanediyl), .alpha[3-[1,3,3,3-	(CAS No) 67674-67-3	0.1 - 1	Acute Tox. 4 (Inhalation:dust,mist), H332
tetramethyl-1-			Eye Dam. 1, H318
[(trimethysilyl)oxy]disiloxanyl]propyl]-			Aquatic Chronic 2, H411
.omegahydroxy-			
Diethanolamine	(CAS No) 111-42-2	< 0.1	Acute Tox. 4 (Oral), H302
		0.1 - < 0.5	Skin Irrit. 2, H315
			Eye Dam. 1, H318
			Carc. 2, H351
			STOT RE 2, H373
			Aquatic Acute 2, H401

08/06/2015 IEOTT.B-CC EN (English US) 2/12

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

			Aquatic Chronic 3, H412
1-Dodecanamine, N,N-dimethyl-, N-oxide	(CAS No) 1643-20-5	0.1 - 0.3	Acute Tox. 4 (Oral), H302
			Skin Irrit. 2, H315
			Eye Dam. 1, H318
			Aquatic Acute 1, H400
			Aquatic Chronic 2, H411

Full text of H-phrases: see section 16

SECTION 4: FIRST AID MEASURES

Description of First Aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

Inhalation: When symptoms occur: go into open air and ventilate suspected area. Obtain medical attention if breathing difficulty persists.

Skin Contact: Remove contaminated clothing. Drench affected area with water for at least 15 minutes. Obtain medical attention if irritation develops or persists.

Eye Contact: Rinse cautiously with water for at least 60 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.

Ingestion: Rinse mouth. Do NOT induce vomiting. Obtain medical attention.

Most Important Symptoms and Effects Both Acute and Delayed

General: Causes skin irritation. May cause respiratory irritation. Causes serious eye damage. Skin sensitization. Suspected of causing cancer.

Inhalation: May cause respiratory irritation. Irritation of the respiratory tract and the other mucous membranes.

Skin Contact: Causes skin irritation. Redness, pain, swelling, itching, burning, dryness, and dermatitis. May cause an allergic skin reaction.

Eye Contact: Causes serious eye damage. Causes permanent damage to the cornea, iris, or conjunctiva.

Ingestion: Ingestion is likely to be harmful or have adverse effects.

Chronic Symptoms: Suspected of causing cancer.

Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media: Alcohol-resistant foam. Water spray, dry chemical, foam, carbon dioxide (CO₂)

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

Special Hazards Arising From the Substance or Mixture

Fire Hazard: Not considered flammable but may burn at high temperatures.

Explosion Hazard: Product is not explosive. Container may explode in heat of fire.

Reactivity: Hazardous reactions will not occur under normal conditions. Hazardous reactions may occur on contact with certain chemicals. Refer to incompatible materials.

Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Use water spray or fog for cooling exposed containers. Do not get water inside containers. Do not apply water stream directly at source of leak. Remove containers from fire area if this can be done without risk. Do not breathe fumes from fires or vapors from decomposition.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Carbon oxides (CO, CO₂). Hydrocarbons. Nitrogen oxides. Organic compounds.

Other Information: Do not allow run-off from fire fighting to enter drains or water courses.

08/06/2015 EOTT.B-CC EN (English US) 3/12

^{*} A range of concentration as prescribed by Controlled Products Regulations has been used where necessary, due to varying composition. The specific chemical identity and/or exact percentage of composition has been withheld as a trade secret within the meaning of the OSHA Hazard Communication Standard [29 CFR 1910.1200]. In the event of an emergency, chemical identities and exact percentages of the proprietary ingredients may need to be disclosed to emergency personnel upon request.

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Reference to Other Sections

Refer to section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Do not breathe vapor, mist or spray. Do not get in eyes, on skin, or on clothing.

For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Ventilate area. Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit.

Environmental Precautions

Prevent entry to sewers and public waters. Avoid release to the environment.

Methods and Material for Containment and Cleaning Up

For Containment: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Methods for Cleaning Up: Clean up spills immediately and dispose of waste safely. Absorb and/or contain spill with inert material. Transfer spilled material to a suitable container for disposal. If spilled directly onto the ground, remove sufficient soil to ensure material is fully recovered. Contact competent authorities after a spill.

Reference to Other Sections

See Heading 8. Exposure controls and personal protection. See Section 13, Disposal Considerations.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Precautions for Safe Handling: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Avoid breathing vapors, mist, spray. Do not get in eyes, on skin, or on clothing. Use appropriate personal protection equipment (PPE).

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures. Use good housekeeping practices during storage, transfer and handling. Do not eat, drink or smoke when using this product.

Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations.

Storage Conditions: Keep container closed when not in use. Store in a dry, cool and well-ventilated place. Store containers in an upright position. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials.

Incompatible Materials: Strong acids, strong bases, strong oxidizers. Reducing agents.

Specific End Use(s) Cleaner

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

For substances listed in section 3 that are not listed here, there are no established Exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), NIOSH (REL), OSHA (PEL), Canadian provincial governments, or the Mexican government

Diethanolamine (111-42-	2)	
USA ACGIH	ACGIH TWA (mg/m³)	1 mg/m³ (inhalable fraction and vapor)
USA ACGIH	ACGIH chemical category	Skin - potential significant contribution to overall exposure
		by the cutaneous route, Confirmed Animal Carcinogen
		with Unknown Relevance to Humans
USA NIOSH	NIOSH REL (TWA) (mg/m³)	15 mg/m ³
USA NIOSH	NIOSH REL (TWA) (ppm)	3 ppm
Alberta	OEL TWA (mg/m³)	2 mg/m ³
British Columbia	OEL TWA (mg/m³)	2 mg/m ³
Manitoba	OELTWA (mg/m³)	1 mg/m³ (inhalable fraction and vapor)
New Brunswick	OEL TWA (mg/m³)	2 mg/m ³

08/06/2015 EOTT.B-CC EN (English US) 4/12

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

New Brunswick	OFI TWA (******)	0.46
	OELTWA (ppm)	0.46 ppm
Newfoundland & Labrador	OELTWA (mg/m³)	1 mg/m³ (inhalable fraction and vapor)
Nova Scotia	OEL TWA (mg/m³)	1 mg/m³ (inhalable fraction and vapor)
Nunavut	OEL STEL (mg/m³)	26 mg/m ³
Nunavut	OEL STEL (ppm)	6 ppm
Nunavut	OEL TWA (mg/m³)	13 mg/m ³
Nunavut	OELTWA (ppm)	3 ррт
Northwest Territories	OEL STEL (mg/m³)	26 mg/m ³
Northwest Territories	OEL STEL (ppm)	6 ppm
Northwest Territories	OELTWA (mg/m³)	13 mg/m³
Northwest Territories	OELTWA (ppm)	3 ррт
Ontario	OEL TWA (mg/m³)	1 mg/m³ (inhalable fraction and vapor)
Prince Edward Island	OELTWA (mg/m³)	1 mg/m³ (inhalable fraction and vapor)
Québec	VEMP (mg/m³)	13 mg/m ³
Québec	VEMP (ppm)	3 ррт
Saskatchewan	OEL STEL (mg/m³)	4 mg/m³
Saskatchewan	OEL TWA (mg/m³)	2 mg/m³

Exposure Controls

Appropriate Engineering Controls: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed.

Personal Protective Equipment: Protective goggles. Gloves. Protective clothing. Insufficient ventilation: wear respiratory protection.









Materials for Protective Clothing: Chemically resistant materials and fabrics.

Hand Protection: Wear protective gloves. **Eye Protection:** Chemical safety goggles.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: In case of insufficient ventilation, wear suitable respiratory equipment.

Other Information: When using, do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Properties

Physical State : Liquid

Appearance : Blue thick liquid

Odor : Pine

Odor Threshold : Not available

pH : 9

Evaporation Rate Not available **Melting Point** Not available **Freezing Point** Not available **Boiling Point** > 100 °C (> 212 °F) **Flash Point** > 100 °C (> 212 °F) **Auto-ignition Temperature** Not available Not available **Decomposition Temperature** Flammability (solid, gas) Not available Not available **Lower Flammable Limit Upper Flammable Limit** Not available **Vapor Pressure** Not available

08/06/2015 EOTT.B-CC EN (English US) 5/12

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Relative Vapor Density at 20 °C : Not available
Relative Density : Not available
Specific Gravity : 1.023 at 20 °C
Solubility : Soluble in water.
Partition Coefficient: N-Octanol/Water : Not available
Viscosity : Not available

Explosion Data – Sensitivity to Mechanical Impact: Not expected to present an explosion hazard due to mechanical impact.

Explosion Data – Sensitivity to Static Discharge: Not expected to present an explosion hazard due to static discharge.

SECTION 10: STABILITY AND REACTIVITY

<u>Reactivity</u>: Hazardous reactions will not occur under normal conditions. Hazardous reactions may occur on contact with certain chemicals. Refer to incompatible materials.

Chemical Stability: Stable under recommended handling and storage conditions (see section 7).

Possibility of Hazardous Reactions: Hazardous polymerization will not occur.

Conditions to Avoid: Direct sunlight, extremely high or low temperatures, and incompatible materials.

Incompatible Materials: Strong acids, strong bases, strong oxidizers. Reducing agents.

<u>Hazardous Decomposition Products</u>: Carbon oxides (CO, CO₂). Nitrogen oxides. Hydrocarbons. Sodium oxides. Sulfur oxides. Metal oxides.

SECTION 11: TOXICOLOGICAL INFORMATION

Information on Toxicological Effects - Product

Acute Toxicity: Not classified **ID50 and IC50 Data:** Not available

Skin Corrosion/Irritation: Causes skin irritation.

pH: 9

Serious Eye Damage/Irritation: Causes serious eye damage.

pH: 9

Respiratory or Skin Sensitization: May cause an allergic skin reaction.

Germ Cell Mutagenicity: Not classified

Teratogenicity: Not available

Carcinogenicity: Suspected of causing cancer.

Specific Target Organ Toxicity (Repeated Exposure): Not classified

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): May cause respiratory irritation.

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: May cause respiratory irritation. Irritation of the respiratory tract and the other mucous membranes.

Symptoms/Injuries After Skin Contact: Causes skin irritation. Redness, pain, swelling, itching, burning, dryness, and dermatitis. May cause an allergic skin reaction.

Symptoms/Injuries After Eye Contact: Causes serious eye damage. Causes permanent damage to the cornea, iris, or conjunctiva.

Symptoms/Injuries After Ingestion: Ingestion is likely to be harmful or have adverse effects.

Chronic Symptoms: Suspected of causing cancer.

Information on Toxicological Effects - Ingredient(s)

ID50 and LC50 Data:

1-Dodecanamine, N,N-dimethyl-, N-oxide (1643-20-5)		
ATE US (oral)	500.00 mg/kg body weight	
Dodecanamide, N,N-bis(2-hydroxyethyl)- (120-40-1)		
ID50 Oral Rat	2700 mg/kg	
Diethanolamine (111-42-2)		
ID50 Oral Rat	1820 mg/kg	

08/06/2015 EOTT.B-CC EN (English US) 6/12

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Sulfonic acids, C14-16-alkane hydroxy and C14-16-alkene, sodium salts (68439-57-6)		
ID50 Oral Rat	2310 mg/kg	
ID50 Dermal Rabbit	6300 mg/kg	
Sodium lauryl sulfate (151-21-3)		
ID50 Oral Rat	1288 mg/kg	
ID50 Dermal Rat	> 2000 mg/kg	
ID50 Dermal Rabbit	580 mg/kg	
IC50 Inhalation Rat	> 3900 mg/m³ (Exposure time: 1 h)	
ATE US (dust, mist)	1.50 mg/l/4h	
Poly(oxy-1,2-ethanediyl), .alpha[3-[1,3,3,3-tetramethyl-1-[(trimethylsilyl)oxy]disiloxanyl]propyl]omegahydroxy- (67674-67-3)		
ATE US (dust, mist)	1.50 mg/l/4h	
Pine oil (8002-09-3)		
ID50 Oral Rat	3200 mg/kg	
ID50 Dermal Rat	5 g/kg	
IC50 Inhalation Rat	> 3790 mg/m ³	
Diethanolamine (111-42-2)		
IARC Group	2B	
OSHA Hazard Communication Carcinogen List	In OSHA Hazard Communication Carcinogen list.	

SECTION 12: ECOLOGICAL INFORMATION

Toxicity

Ecology - **General:** Harmful to aquatic life. Harmful to aquatic life with long lasting effects.

1-Dodecanamine, N,N-dimethyl-, N-oxide (1643-20-5)			
0.11 mg/l (72 hour)			
4460 (4460 - 4980) mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-			
through])			
55 mg/l (Exposure time: 48 h - Species: Daphnia magna)			
1200 (1200 - 1580) mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])			
2.1 (2.1 - 2.3) mg/l (Exposure time: 96 h - Species: Pseudokirchneriella subcapitata)			
2.2 mg/l (Exposure time: 96 h - Species: Pseudokirchneriella subcapitata [Static])			
0.78 mg/l			
nd C14-16-alkene, sodium salts (68439-57-6)			
4.2 mg/l (Exposure time: 96 h - Species: Brachydanio rerio [static])			
4.53 mg/l (Ceriodaphnia sp)			
12.2 mg/l (Exposure time: 96 h - Species: Brachydanio rerio [semi-static])			
5.2 mg/l (Water quality - Marine Algal Growth Inhibition Test with Skeletonema costatum			
and Phaeodactylum tricornutum)			
Sodium lauryl sulfate (151-21-3)			
8 (8 - 12.5) mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])			
1.8 mg/l (Exposure time: 48 h - Species: Daphnia magna)			
15 (15 - 18.9) mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])			
Pine oil (8002-09-3)			
17 - 28 mg/l (Exposure time: 48 h - Species: Daphnia magna [Flow through])			

POWER PINE WASH & WAX	
Persistence and Degradability	May cause long-term adverse effects in the environment.

Rioaccumulative Potential

Divaccumulative Potential	
POWER PINE WASH & WAX	
Bioaccumulative Potential	Not established.

08/06/2015 EOTT.B-CC EN (English US)

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Diethanolamine (111-42-2)	
BCF Fish 1	(no significant bioconcentration)
Log Pow	-2.18 (at 25 °C)
Sodium lauryl sulfate (151-21-3)	
BCF Fish 1	(will not bioconcentrate)
Log Pow	1.6

Mobility in Soil Not available

Other Adverse Effects

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Recommendations: Dispose of contents/container in accordance with local, regional, national, territorial, provincial, and international regulations

Additional Information: Container may remain hazardous when empty. Continue to observe all precautions.

Ecology – Waste Materials: Avoid release to the environment. This material is hazardous to the aquatic environment. Keep out of sewers and waterways.

SECTION 14: TRANSPORT INFORMATION

In Accordance With ICAO/IATA/DOT/TDG/IMDG

UN Number Not regulated for transport

<u>UN Proper Shipping Name</u> Not regulated for transport

Transport Hazard Class(es) Not regulated for transport

Additional Information Not available

Transport by sea Not regulated for transport

Marine Pollutant No

Air transport Not regulated for transport

SECTION 15: REGULATORY INFORMATION

US Federal Regulations

US State Regulations
Diethanolamine (111-42-2)

U.S. - California - Proposition 65 - Carcinogens List

<u>US rederai Regulations</u>		
POWER PINE WASH & WAX		
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard	
	Delayed (chronic) health hazard	
1-Dodecanamine, N,N-dimethyl-, N-oxide (1643-20-5)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Dodecanamide, N,N-bis(2-hydroxyethyl)- (120-40-1)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Diethanolamine (111-42-2)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Listed on United States SARA Section 313		
SARA Section 313 - Emission Reporting	1.0 %	
Sulfonic acids, C14-16-alkane hydroxy and C14-16-alkene, sod	ium salts (68439-57-6)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
Sodium lauryl sulfate (151-21-3)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
Poly(oxy-1,2-ethanediyl), .alpha[3-[1,3,3,3-tetramethyl-1-[(trimethylsilyl)oxy]disiloxanyl]propyl]omegahydroxy- (67674-67-3)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
Pine oil (8002-09-3)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		

08/06/2015 EOTT.B-CC EN (English US) 8/12

California to cause cancer.

WARNING: This product contains chemicals known to the State of

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

1-Dodecanamine, N,N-dimethyl-, N-oxide (1643-20-5)

- U.S. Texas Effects Screening Levels Long Term
- U.S. Texas Effects Screening Levels Short Term

Dodecanamide, N,N-bis(2-hydroxyethyl)- (120-40-1)

- U.S. Texas Effects Screening Levels Long Term
- U.S. Texas Effects Screening Levels Short Term

Diethanolamine (111-42-2)

- U.S. California SCAQMD Toxic Air Contaminants Non-Cancer Chronic
- U.S. California Toxic Air Contaminant List (AB 1807, AB 2728)
- U.S. Connecticut Hazardous Air Pollutants HLVs (30 min)
- U.S. Connecticut Hazardous Air Pollutants HLVs (8 hr)
- U.S. Delaware Pollutant Discharge Requirements Reportable Quantities
- U.S. Idaho Non-Carcinogenic Toxic Air Pollutants Acceptable Ambient Concentrations
- U.S. Idaho Non-Carcinogenic Toxic Air Pollutants Emission Levels (ELs)
- U.S. Illinois Toxic Air Contaminant Carcinogens
- **U.S.** Illinois Toxic Air Contaminants
- U.S. Louisiana Reportable Quantity List for Pollutants
- U.S. Maine Air Pollutants Hazardous Air Pollutants
- RTK U.S. Massachusetts Right To Know List
- U.S. Massachusetts Toxics Use Reduction Act
- U.S. Michigan Occupational Exposure Limits TWAs
- U.S. Michigan Polluting Materials List
- U.S. Minnesota Chemicals of High Concern
- U.S. Minnesota Hazardous Substance List
- U.S. Minnesota Permissible Exposure Limits TWAs
- U.S. New Hampshire Regulated Toxic Air Pollutants Ambient Air Levels (AALs) 24-Hour
- U.S. New Hampshire Regulated Toxic Air Pollutants Ambient Air Levels (AALs) Annual
- U.S. New Jersey Discharge Prevention List of Hazardous Substances
- U.S. New Jersey Environmental Hazardous Substances List
- RTK U.S. New Jersey Right to Know Hazardous Substance List
- U.S. New Jersey Special Health Hazards Substances List
- U.S. New York Occupational Exposure Limits TWAs
- U.S. New York Reporting of Releases Part 597 List of Hazardous Substances
- U.S. North Dakota Air Pollutants Guideline Concentrations 8-Hour
- U.S. California Safer Consumer Products Initial List of Candidate Chemicals and Chemical Groups
- RTK U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- RTK U.S. Pennsylvania RTK (Right to Know) List
- U.S. Rhode Island Air Toxics Acceptable Ambient Levels Annual
- U.S. South Carolina Toxic Air Pollutants Maximum Allowable Concentrations
- U.S. South Carolina Toxic Air Pollutants Pollutant Categories
- U.S. Tennessee Occupational Exposure Limits TWAs
- U.S. Texas Effects Screening Levels Long Term
- U.S. Texas Effects Screening Levels Short Term
- U.S. Vermont Permissible Exposure Limits TWAs
- U.S. Washington Permissible Exposure Limits STELs
- U.S. Washington Permissible Exposure Limits TWAs
- U.S. Wisconsin Hazardous Air Contaminants All Sources Emissions From Stack Heights 25 Feet to Less Than 40 Feet
- U.S. Wisconsin Hazardous Air Contaminants All Sources Emissions From Stack Heights 40 Feet to Less Than 75 Feet
- U.S. Wisconsin Hazardous Air Contaminants All Sources Emissions From Stack Heights 75 Feet or Greater
- U.S. Wisconsin Hazardous Air Contaminants All Sources Emissions From Stack Heights Less Than 25 Feet

Sulfonic acids, C14-16-alkane hydroxy and C14-16-alkene, sodium salts (68439-57-6)

- U.S. Texas Effects Screening Levels Long Term
- U.S. Texas Effects Screening Levels Short Term

08/06/2015 EOTT.B-CC EN (English US) 9/12

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

odium lauryl sulfate (151-21-3)	
J.S Texas - Effects Screening Levels - Long Term	
J.S Texas - Effects Screening Levels - Short Term	
Pine oil (8002-09-3)	
TTK - U.S New Jersey - Right to Know Hazardous Substance List	
J.S Texas - Effects Screening Levels - Long Term	
J.S Texas - Effects Screening Levels - Short Term	

Canadian Regulations

POWER PINE WASH & WAX	
WHMIS Classification	Class D Division 2 Subdivision A - Very toxic material causing other toxic effects
	Class D Division 2 Subdivision B - Toxic material causing other toxic effects

1-Dodecanamine, N,N-dimethyl-, N-oxide (1643-20-5)		
Listed on the Canadian DSL (Domestic Substances List)		
Listed on the Canadian IDL	(Ingredient Disclosure List)	
IDL Concentration 1 %		
WHMIS Classification	Class D Division 1 Subdivision B - Toxic material causing immediate and serious toxic effects	
	Class D Division 2 Subdivision B - Toxic material causing other toxic effects	
Dodecanamide, N,N-bis(2-l	hydroxyethyl)- (120-40-1)	
Listed on the Canadian DSL (Domestic Substances List)		
WHMIS Classification	Class D Division 2 Subdivision B - Toxic material causing other toxic effects	
Diethanolamine (111-42-2)		
Listed on the Canadian DSL	(Domestic Substances List)	
Listed on the Canadian IDL (Ingredient Disclosure List)		
IDL Concentration 1 %		
WHMIS Classification	Class D Division 2 Subdivision A - Very toxic material causing other toxic effects	
	Class D Division 2 Subdivision B - Toxic material causing other toxic effects	
Sulfonic acids, C14-16-alkar	ne hydroxy and C14-16-alkene, sodium salts (68439-57-6)	
Listed on the Canadian DSL (Domestic Substances List)		
WHMIS Classification	Class D Division 2 Subdivision B - Toxic material causing other toxic effects	
Sodium lauryl sulfate (151-21-3)		
Listed on the Canadian DSL (Domestic Substances List)		
Listed on the Canadian IDL (Ingredient Disclosure List)		
IDL Concentration 1 %		
WHMIS Classification	Class B Division 4 - Flammable Solid	
	Class D Division 1 Subdivision B - Toxic material causing immediate and serious toxic effects	
	Class D Division 2 Subdivision B - Toxic material causing other toxic effects	
Poly(oxy-1,2-ethanediyl), .a	alpha[3-[1,3,3,3-tetramethyl-1-[(trimethylsilyl)oxy]disiloxanyl]propyl]omegahydroxy- (67674-67-3)	
Listed on the Canadian DSL	(Domestic Substances List)	
WHMIS Classification	Class D Division 1 Subdivision B - Toxic material causing immediate and serious toxic effects	
	Class D Division 2 Subdivision B - Toxic material causing other toxic effects	
Pine oil (8002-09-3)		
Listed on the Canadian DSL (Domestic Substances List)		
WHMIS Classification	Class B Division 3 - Combustible Liquid	
	Class D Division 2 Subdivision B - Toxic material causing other toxic effects	

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.

08/06/2015 EOTT.B-CC EN (English US) 10/12

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Revision Date : 08/06/2015

Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA

Hazard Communication Standard 29 CFR 1910.1200.

GHS Full Text Phrases:

Acute Tox. 3 (Dermal)	Acute toxicity (dermal) Category 3
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Aquatic Acute 2	Hazardous to the aquatic environment - Acute Hazard Category 2
Aquatic Acute 3	Hazardous to the aquatic environment - Acute Hazard Category 3
Aquatic Chronic 2	Hazardous to the aquatic environment - Chronic Hazard Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment - Chronic Hazard Category 3
Asp. Tox. 1	Aspiration hazard Category 1
Carc. 2	Carcinogenicity Category 2
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Liq. 3	Flammable liquids Category 3
Flam. Sol. 2	Flammable solids Category 2
Skin Irrit. 2	Skin corrosion/irritation Category 2
Skin Sens. 1	Skin sensitization Category 1
STOT RE 2	Specific target organ toxicity (repeated exposure) Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H226	Flammable liquid and vapor
H228	Flammable solid
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H311	Toxic in contact with skin
Н315	Causes skin irritation
Н317	May cause an allergic skin reaction
Н318	Causes serious eye damage
Н319	Causes serious eye irritation
Н332	Harmful if inhaled
Н335	May cause respiratory irritation
H351	Suspected of causing cancer
Н373	May cause damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H401	Toxic to aquatic life
H402	Harmful to aquatic life
H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects
	<u> </u>

NFPA Health Hazard

2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt

medical attention is given.


NFPA Fire Hazard : 1 - Must be preheated before ignition can occur.

NFPA Reactivity : 0 - Normally stable, even under fire exposure conditions,

and are not reactive with water.







Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Starbrite®

Phone Number: (954)587-6280

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

NA GHS SDS

08/06/2015 EOTT.B-CC EN (English US) 12/12